Reolink-Go-PT-Plus-IP-Camera-Specifications				
	Model	Reolink Go PT Plus		
Video & Audio	Image Sensor	1/3" CMOS Sensor		
	Video Resolution	2560 x 1440 (4.0 megapixel) at 15 frames/sec		
	Video Format	H.265		
	Field of View	Fixed lens, horizontal: 95 °, vertical: 57 °, 115 ° diagonal		
	Infrared Night Vision	Up to 10 meters (33ft) (LED: 6pcs/14mil/850nm)		
	Digital Zoom	16X digital zoom		
	Audio	Two-way audio		
PIR Detection &	Smart Alarm	PIR detection/human detection/vehicle detection		
	PIR Detecting Distance	Adjustable up to 10m (33ft)		
	PIR Detecting Angle	120 °horizontal		
	Audio Alert	Customizable verbal alerts		
	Recording	Motion-triggered recording		
	Other Alerts	Instant email alerts and push notifications		
3G/4G	Frequency Bands	Europe LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8		
		America LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5		
		Australia LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8		
	Transmission Data	LTE FDD: Max. 10Mbps (DL), Max. 5Mbps (UL)		
		LTE TDD: Max. 8.96Mbps (DL), Max. 3.1Mbps (UL)		
		HSPA+: Max. 42Mbps (DL), Max. 5.76Mbps (UL)		
		UMTS: Max. 384Kbps (DL), Max. 384Kbps (UL)		

Power	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)	
	Solar	Reolink Solar Panel (optional)	
	DC Power	5V/2A USB power adapter	
Storage	Local Storage	Micro SD card slot (supports Max. 128GB; includes a 32GB micro SD card)	
	Cloud Storage	Supports Reolink Cloud (available in some countries)	
Smart Home	Smart Home	Works with Google Assistant	
Working Environment	Operating Temperature	-10 ℃ to 55 ℃ (14 F to 131 F)	
	Weather Resistance	IP64 Weatherproof	
Size & Weight	Size	Ф98 x 112mm (Ф3.7 x 4.4 in)	
	Weight (Battery Included)	485g (17.1 oz)	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.	





- Antenna
- 2 Battery Status LED 3 Micro USB Port 4 Power Switch

- 6 Reset Hole
- 6 Nano SIM Card Slot 7 Micro SD Card Slot