

Reolink-Duo-PoE-IP-Camera-Specifications		
	Model	Reolink Duo PoE
Video & Audio	Image Sensor	1/3" CMOS Sensors
	Video Resolution	Default: 2560X1440 (4.0 Megapixels) at 22 frames/sec
	Lens	f = 4.0 mm fixed, F = 2.0
	Video Format	H.264
	Field of View	Horizontal: 150°
		Vertical: 44°
	Day & Night	Auto-switching with IR cut filter
	Infrared Night Vision	30 Meters (LED: 6pcs/20mil/850nm)
	Color Night Vision	Spotlight: 8pcs/5W/6500K/560 Lumens
Power	Audio	Two-way audio
	POE	IEEE 802.3af, 48V Active
	DC Power	DC 12V=2A, <12W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
	Storage	Micro SD card slot (Max. 256GB)
	Audio	Built-in microphone and speaker
Software Features	Frame Rate	Mainstream: 2fps - 25fps (default: 22fps)
		Substream: 4fps - 15fps (default: 10fps)
	Code Rate	Mainstream: 1024Kbps -5120Kbps (default: 4096Kbps)
		Substream: 64Kbps - 512Kbps (default: 256Kbps)
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/person detection/vehicle detection
	Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Working Environment	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
Size & Weight	Waterproof	IP66
	Dimension	195x103x56 mm
	Weight	650g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/



- 1 Lens
- 2 Daylight Sensor
- 3 Spotlight
- 4 IR LED
- 5 Mic
- 6 Mounting Bracket



- 1 Micro SD Card Slot
- 2 Reset Button
- 3 Speaker



- 1 Power
- 2 Network
- 3 Waterproof Lid

