

**DS-PA201PS-32WA**

- 
- Simple and elegant appearance design
  - Wi-Fi network for cloud communication
  - Friendly app interface makes installation and use easier
  - Up to 2000 m radio signal transmission range in open space

## ▪ Specification

Capacity	
Areas	8
Wireless zones	32
Wireless keypads	4
Wireless sounders	4
Wireless keyfobs	16
Logs	1000
ARC	1
Installer	3
Admin	1
User	12
Communication	
Transmission technology	912.5~917.4 MHz
Transmission range (free space)	up to 2,000 m
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
Encryption	AES-128
Ethernet	1 8P8C socket
Ethernet speed	≤10Mbps
Wi-Fi	802.11 b/g/n
Cellular	4G
SIM slots	1
Notifications	
APP notifications	Yes
SMS notifications	Yes
Calls notifications	Yes
ARC notifications	Yes
Event types	Alarms Faults System Events Operations
Software features	
Protocol	SIA-DCS *SIA-DCS ADM-CID *ADM-CID OTAP Other proprietary protocols
Upgrade OTA	Yes
Hardware features	
Tamper-Proof	Yes
Indication	
Indication method	LED

Electrical characteristics	
Power consumption	max current: 0.2 A quiescent current: 90 mA
Mains power	110-240 V~, 50/60 Hz
Built-in backup battery	Yes
Battery life	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
Wireless transmission	
RF frequency	915 MHz
General	
Dimension (W×H×D)	165 x 165 x 37.5 mm
Shell material	165 x 165 x 37.5 mm
Weight	410 g
Operation temperature	-10 °C to +55 °C
Operation humidity	10% to 90%

- **Available Model**

DS-PA201PS-32WA

- **Accessory**

- **Included**

**DS-PC201N  
LAN Module**



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

