

DS-1005KI USB Keyboard



- Full-featured USB keyboard
- Supports various cameras, NVRs, DVRs and also iVMS 4200
- Flexible 4-axis joystick
- Buttons can be used to perform powerful functions



Specification

Interface					
USB Interface	USB 2.0, DirectX				
Serial Interface	Joystick (3-axis control, ,rotating zoom)				
General					
Working Temperature	-10°C ~ 55°C (14°F ~ 131°F)				
Working Humidity	10%~90% (Non-condensing)				
Dimensions (W × H × D)	167×116 ×177.5mm ,(6.57"× 4.57"×6.99")				
Power Supply	5V DC via USB				
System					
Operating System Supported	Windows XP, Windows 7, Windows 8, Windows 8.1				
Certification					
Obtained Certification	CE-EMC/CE-LVD/ROHS/CB/UL/FCC-SDoC/IC-VoC/BIS/RCM				

Available Model

DS-1005KI DS-1005KI/ONCU/DP-1005KI DS-1005KI/ZAO Hikvision DS-1005KI/HIK USA

Accessory

Optional

• • • • • • • • •				
DS-2DE4425IW-DE(S6) 4-inch 4 MP 25X Powered by DarkFighter IR Network Speed Dome	DS-2DE4415IW-DE(S6) 4-inch 4 MP 15X Powered by DarkFighter IR Network Speed Dome	DS-2DE7425IW-AE(S6) 7-inch 4 MP 25X Powered by DarkFighter IR Network Speed Dome	DS-2DE7232IW-AE(S6) 7-inch 2 MP 32X Powered by DarkFighter IR Network Speed Dome	DS-2DE5225W-AE3(T5) 2 MP 25X Powered by DarkFighter Network Speed Dome
		INT VIEW		
DS-2DE5232W-AE3(T5) 2 MP 32X Powered by DarkFighter Network Speed Dome	DS-I215(D)#RUS 4-inch 2 MP 15X Powered by DarkFighter IR Network Speed Dome	DS-2DE5232IW-AE(S6)#ASIA 5-inch 2 MP 32X Powered by DarkFighter IR Network Speed Dome		

۲





See Far, Go Further



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

