

E1-Zoom-IP-Camera-Specifications		
	Model	E1 Zoom
Hardware Features	Image Sensor	1/2.7" CMOS Sensor
	Display Resolution	2560x1920 (5 Megapixels)
	Lens	f=2.8-8mm Autofocus, F=1.6, with IR Cut
	Zoom	3X Optical Zoom
	Angle of View	Horizontal: 48° - 98°
		Vertical: 37° - 75°
	Pan/Tilt Angle	Horizontal: 355°
		Vertical: 50°
	Minimum Illumination	0 Lux (with IR Illuminator)
	IR Distance	12 Meters (40ft) (LED: 10pcs/14mil/850nm)
	Dimension	Φ80x111mm
	Weight	250g
	Power Input	DC 5.0V/1A
Software Features	Interface	Power Interface
		Micro SD Card Slot
		Built-in Microphone and Speaker
		Reset Button
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Image Compression	H.264
	Maximal Frame Rate	20fps
	Code Rate	1024Kbps ~ 4096Kbps (Default: 4096Kbps)
	Audio	Two-Way Audio
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Wireless Features	Record Mode	Motion Recording
	Alarm	Siren; Customized Voice-Recordable Alerts
	Works with	Google Assistant; Reolink Cloud *available in some countries
Other Parameters	Wireless Standard	IEEE 802.11a/b/g/n
		2.4/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
	Temperature	Operating Temperature: -10°C~+55°C
		Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20% ~ 85%
		Storage Humidity: 10% ~ 90%
	Waterproof	No

