

Reolink-Go-PT-IP-Camera-Specifications		
	Model	Reolink Go PT
Video & Audio	Image Sensor	Starlight CMOS Image Sensor
	Video Resolution	1080p HD at 15 frames/sec
	Video Format	H.264
	Field of View	Fixed Lens, 105° Diagonal
	Pan/Tilt Angle	Horizontal: 355°
		Vertical: 140°
	Night Vision	Up to 10m (33 ft)
	Digital Zoom	6x Digital Zoom
PIR Detection & Alerts	Audio	High-Quality Speaker and Microphone
	PIR Detecting Distance	Adjustable up to 10m (33 ft)
	PIR Detecting Angle	90° Horizontal
	Audio Alert	Customized Verbal Alerts
	Other Alerts	Instant Email Alerts and Push Notifications
3G/4G Bandwidth	Frequency Bands	Europe: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		the United States: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
		Australia: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
	Transmission Data	LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL)
		LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL)
		HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL)
		UMTS: Max 384Kbps (DL), Max 384Kbps (UL)
Power	Battery	6500mAh Rechargeable Battery (Battery Life Varies Based on Settings, Usage & Temperature)
	Solar	Reolink Solar Panel
	DC Power	5V/2A USB Power Adaptor
Storage	Local Storage	with 16GB Micro SD Card
	Cloud Storage	Reolink Cloud * Available in some countries
Working Environment	Operating Temperature	-10° to 55° C (14° to 131° F)
	Weather Resistance	IP64 Weatherproof
Size & Weight	Size	Φ98 x 112mm (Φ3.7 x 4.4 in)
	Weight (Battery included)	485g (17.1 oz)
Warranty	Limited Warranty	2-Year Limited Warranty. For Support, Visit https://support.reolink.com/hc/en-us/

