

	Model	RLC-410
Camera	Image Sensor	1/2.7" CMOS Sensor
	Effective Pixels	2560x1920 (5.0 Megapixels)
	Lens	f=4.0mm F=2.0
	Angle of View	Horizontal: 80°, Vertical: 58°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (100ft) (LED: 18pcs/14mil/850nm)
	Backlight Compensation	Support
	Noise Reduction	3D DNR
Video	Compression	H.264
	Resolution	Main Stream: 2560x1920, 2560x1440, 2048x1536, 2304x1296; Sub Stream: 640x480
	Bitrate	Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps
	Frame Rate	Main Stream@30fps, Sub Stream@6fps
Audio	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
	Storage	Built-in Micro SD socket, support motion detect record
General	Power Supply	DC12V & PoE (IEEE 802.3af)
	Power Consumption	<10W
	Working Environment	-10°C~+55°C(14°F~131°F), 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ67 x 186mm
	Weight	350g

