

RLN16-410-4K-PoE-NVR-Specifications		
Hardware	Model	RLN16-410 (4K Version)
	Hardware	V2
Video/Audio Input	IP Video Input	PoE IP Camera x 16
	Audio Input	Cameras with Built-in Mic
Video/Audio Output	Video Output	VGA, HDMI
	Display Resolution	HDMI: 3840*2160, 1920*1080, 1280*1024, 1280*720, 1024*768
		VGA: 1920*1080, 1280*1024, 1280*720, 1024*768
	Audio Output	1-Channel, RCA
Decoding	Video Format	H.265, H.264
	Live View/Playback Resolution	3840*2160, 2560x1920, 2560*1440, 2048*1536, 2304*1296, 1080P, 720P
	Synchronous Playback	1-4 Channel(s)
Storage	SATA	2 SATA Interfaces for 2HDDs
	Capacity	Up to 6TB Capacity for Each HDD
	External HDD	NO
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface for LAN/WAN
		16, RJ-45 10/100 Mbps Self-Adaptive PoE Ethernet Interface for IP Cameras
PoE	Max. Power Consumption/Port	25W
	Supported Standard	IEEE 802.3 af/at
Network	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browsers Supported	Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users
General	Power Supply	DC 48V/2.5A
	Power Consumption	<10W (Without HDD & PoE)
	Working Environment	Temperature: -10°C ~+55°C (14°F~131°F); Humidity: 10%~90%
	Dimensions (mm)	330 x 45 x 285
	Weight	1.8 kg (Without HDD)
Warranty	Limited Warranty	2-Year Limited Warranty. For Support, Visit https://support.reolink.com/hc/en-us/ .

