


RLK8-820D4-A-NVR-Kit-NVR-Specifications		
	Model	RLN8-410
Hardware	Hardware	V2
Video/Audio Input	IP Video Input	PoE IP Camera x 8
	Audio Input	Cameras with Built-in Mic
Video/Audio Output	HDMI Output	3840x2160, 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768
	VGA Output	1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768
	Audio output	1CH RCA
Decoding	Live View/Playback Resolution	3840x2160, 2560x1920, 2560x1440, 2048x1536, 2304x1296, 1080p, 720p
	Video Format	H.265/H.264
	Synchronous Playback	Up to 4 Channels
HDD	SATA Devices	1 x 2TB SATA HDD
	Maximum Capacity	12TB (Maximum 6TB HDD/Port)
	External HDD	1 x eSATA
External Interface	USB Interface	2 x USB 2.0
	Network Interface	RJ45,10M/100M Ethernet, 8 Network Ports for IP camera, 1 Giga Network Port for LAN/WAN
PoE	Interface	8 Independent 100 Mbps PoE Network Interfaces
	Max. Power Consumption	25W
	Supported Standard	IEEE 802.3at
Network	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browser Supported	IE, Firefox, Chrome
	OS Supported	PC: Windows, Mac OS; SmartPhone: iOS, Android
	Max. User Access	20 Users
General	Power Supply	DC 48V/2A
	Power Consumption	<10W (Without HDD&PoE)
	Working Environment	Temperature: -10℃~+45℃ (14°F~113°F); Humidity: 10%~90%
	Dimensions (mm)	260(W) x 41(H) x 230(D)
	Weight (w/o HDD)	1.2 kg



Only Manual Rotation