

RLC-511WA-IP-Camera-Specifications		
	Model	RLC-511WA
Video & Audio	Image Sensor	1/2.7" CMOS Sensor
	Video Resolution	Default: 2560 x 1920 (5.0 megapixels) at 20 frames/sec
	Lens	f=2.7-13.5mm F=1.6-3.3, with IR cut
	Video Format	H.264
	Field of View	Horizontal: 96°- 27° Vertical: 69°- 21°
	Day & Night	IR-Cut filter with auto-switching
	Infrared Night Vision	Up to 30 meters (LED: 4pcs/28mil/850nm)
	Color Night Vision	Up to 30 meters (LED: 5pcs/4W/6500K/450 lumens)
	Audio	Two-Way audio
	DC Power	DC 12.0V~1A, <12W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps RJ45
	Storage	Micro SD card slot (Max. 256GB)
	Audio	Built-in microphone and speaker
Software Features	Frame Rate	Mainstream: 2fps - 30fps (default: 20fps) Substream: 4fps - 15fps (default: 10fps)
	Code Rate	Mainstream: 1024Kbps - 8192Kbps (default: 4096Kbps) Substream: 64Kbps - 512Kbps (default: 256Kbps)
	Browsers Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/human detection/vehicle detection
	Record Modes	Motion recording (default)/scheduled recording
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
WiFi	Work with	Google Assistant
	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4GHz/5GHz
Working Environment	Wireless Security	WPA-PSK/WPA2-PSK
	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
Size & Weight	Waterproof	IP66
	Dimension	Φ80 x 72x 238mm
	Weight	838g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

