

Reolink-Duo-WiFi-IP-Camera-Specifications		
	Model	Reolink Duo WiFi
Video & Audio	Image Sensor	1/3" CMOS Sensors
	Video Resolution	Default: 2560X1440 (4.0 Megapixels) at 15 frames/sec
	Lens	f= 4.0 mm fixed, F= 2.0
	Video Format	H.264
	Field of View	Horizontal: 150°
		Vertical: 44°
	Day & Night	Auto-switching with IR cut filter
	Infrared Night Vision	30 Meters (LED: 6pcs/20mil/850nm)
	Color Night Vision	Spotlight: 8pcs/5W/6500K/560 Lumens
	Audio	Two-way audio
Power	DC Power	DC 12.0V=2A, <15W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
	Storage	Micro SD card slot (Max. 256GB)
	Audio	Built-in microphone and speaker
Software Features	Frame Rate	Mainstream: 2fps - 25fps (default: 15fps)
		Substream: 4fps - 15fps (default: 10fps)
	Code Rate	Mainstream: 1024Kbps - 5120Kbps (default: 3072Kbps)
		Substream: 64Kbps - 512Kbps (default: 256Kbps)
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/person detection/vehicle detection
	Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)

Wi-Fi	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4GHz/5GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Working Environment	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
	Waterproof	IP66
Size & Weight	Dimension	195x103x56 mm
	Weight	680g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/



1 Antenna

2 Lens

3 Daylight Sensor

4 Spotlight

5 IR LED

6 Mic

7 Mounting Bracket



1 Micro SD Card Slot

2 Reset Button

3 Speaker



1 Power

2 Network

3 Waterproof Lid

