

Picture		
Model		RP-PN16
Video/Audio Input	IP Video Input	Up to 24 IP Cameras (Max.16 wired cameras) Up to 16 MP resolution
	Audio Input	Cameras with built-in MIC
	Incoming Bandwidth	400Mbps
	Outgoing Bandwidth	400Mbps
Video/Audio Output	Video Output	1 HDMI, 1 VGA
	Display Resolution	HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
		Audio Output 1 audio out channel, RCA
Decoding	Video Compression	H.265 / H.264
	Live View/Playback Resolution	7680X2160, 4608X1728, 4512X2512, 4096X3072, 3840X2160, 2560*2560, 2560X1920, 2560X1440, 2048X1536, 2304X1296,1080P,720P
	Synchronous Playback	1-4 channels (Supports only 1-channel playback if you view it in 8MP or higher resolution)
HDD	SATA	2 SATA interfaces for 2 HDDs (with or without 4TB HDD)
	External HDD	N/A
	Capacity	Up to 32TB (up to 16TB capacity for one HDD)
External Interfaces	USB Interface	2 x USB 2.0
	Network Interface	16 x RJ-45, 10/100 Mbps self-adaptive PoE Ethernet interface (for IP cameras) 1 x RJ-45, 10/100/1000 Mbps self-adaptive (for LAN/WAN)
PoE	Max. Power per Port	25W
	Supported Standard	IEEE 802.3 af/at
Network	Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, RTMP, SMTP, SSL/TLS, DNS, DDNS, NTP,FTP
	Browsers Supported	Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; Smart phone: iOS, Android
	User Access	20 Users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Other Features	Heat Map	Yes
General	Power Supply	DC 53V/3.77A
	Power Consumption	<10W (without HDD & PoE)
	Working Environment	Temperature: -10°C ~ + 45°C (14°F ~ 113°F); Humidity: 10% ~ 90%
	Dimensions	330mmx48mmx272mm
	Weight	2.2kg (without HDD) 2.6kg (with HDD)
Warranty	Limited Warranty	2-year